

**5% AXIAL LEADED RESISTOR**

BRN BLK RED GLD  
**1 0 2**

IN HOUSE P/N: \_\_\_\_\_102  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**1.0k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

RED RED RED GLD  
**2 2 2**

IN HOUSE P/N: \_\_\_\_\_222  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**2.2k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

YEL VIO RED GLD  
**4 7 2**

IN HOUSE P/N: \_\_\_\_\_472  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**4.7k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

BRN BRN RED GLD  
**1 1 2**

IN HOUSE P/N: \_\_\_\_\_112  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**1.1k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

RED YEL RED GLD  
**2 4 2**

IN HOUSE P/N: \_\_\_\_\_242  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**2.4k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

GRN BRN RED GLD  
**5 1 2**

IN HOUSE P/N: \_\_\_\_\_512  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**5.1k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

BRN RED RED GLD  
**1 2 2**

IN HOUSE P/N: \_\_\_\_\_122  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**1.2k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

RED VIO RED GLD  
**2 7 2**

IN HOUSE P/N: \_\_\_\_\_272  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**2.7k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

GRN BLU RED GLD  
**5 6 2**

IN HOUSE P/N: \_\_\_\_\_562  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**5.6k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

BRN ORN RED GLD  
**1 3 2**

IN HOUSE P/N: \_\_\_\_\_132  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**1.3k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

ORN BLK RED GLD  
**3 0 2**

IN HOUSE P/N: \_\_\_\_\_302  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**3.0k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

BLU RED RED GLD  
**6 2 2**

IN HOUSE P/N: \_\_\_\_\_622  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**6.2k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

BRN GRN RED GLD  
**1 5 2**

IN HOUSE P/N: \_\_\_\_\_152  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**1.5k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

ORN ORN RED GLD  
**3 3 2**

IN HOUSE P/N: \_\_\_\_\_332  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**3.3k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

BLU GRY RED GLD  
**6 8 2**

IN HOUSE P/N: \_\_\_\_\_682  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**6.8k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

BRN BLU RED GLD  
**1 6 2**

IN HOUSE P/N: \_\_\_\_\_162  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**1.6k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

ORN BLU RED GLD  
**3 6 2**

IN HOUSE P/N: \_\_\_\_\_362  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**3.6k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

VIO GRN RED GLD  
**7 5 2**

IN HOUSE P/N: \_\_\_\_\_752  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**7.5k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

BRN GRY RED GLD  
**1 8 2**

IN HOUSE P/N: \_\_\_\_\_182  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**1.8k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

ORN WHT RED GLD  
**3 9 2**

IN HOUSE P/N: \_\_\_\_\_392  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**3.9k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

GRY RED RED GLD  
**8 2 2**

IN HOUSE P/N: \_\_\_\_\_822  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**8.2k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

RED BLK RED GLD  
**2 0 2**

IN HOUSE P/N: \_\_\_\_\_202  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**2.0k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

YEL ORN RED GLD  
**4 3 2**

IN HOUSE P/N: \_\_\_\_\_432  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**4.3k Ω**

POWER  
250mW

**5% AXIAL LEADED RESISTOR**

RED BRN RED GLD  
**9 1 2**

IN HOUSE P/N: \_\_\_\_\_912  
 TYPE: Carbon Film  
 MAX VOLTAGE: 250 VDC  
 TOLERANCE: ±5% ←

**9.1k Ω**

POWER  
250mW